


A new development in the Avdel® Speed Fastening range is in the area of miniature fasteners. These have been designed to provide an optimum level of joint performance whilst minimising the amount of space required on the joint surface.

Material	Finish
1.6mm Aluminium alloy (3.5% magnesium) to BS 1473 5154A DIN 1725 AlMg3.5 Werkstoff 3.3535	Natural
2.4mm Aluminium alloy (5% magnesium) to BS 1473 5056A DIN 1725 AlMg5 Werkstoff 3.3555	Natural



A = Head Diameter
 B = Head Thickness
 C = Length
 D = Shank Diameter

BEFORE PLACING

Dimensions

Fastener Size	C		Hole Size		Part Number	Fasteners per pod*	A		B	D
	nom.	max.	min.	max.			Podded	min.	max.	max.
1.6	4.11	1.80	1.93		01110-10400	63	2.54	2.80	0.61	1.78
		6.50	1.80	1.93	01110-10571	42	2.54	2.80	0.61	1.78
2.4	3.56	2.31	2.41		01810-06324	71	3.68	4.19	0.94	2.13
		4.57	2.31	2.41	01810-06314	55	3.68	4.19	0.94	2.13

Dimensions in millimetres

*Nominal value only. Tolerance ±1 fastener per pod.

Please contact your local TFS representative for information on installation tools.