

GB3 Recessed T-Handle

Features

- An extremely useful set that allows our large 'T' handle to be mounted so that the "arms" of the handle do not project above the surface of a panel
- Locking and non-locking models available, supplied as boxed sets.
- 180° rotation as standard, locking in two positions. Rotation can be limited to 90°, LH/RH, or 360° free-movement

Material




- Handle: Steel, bright chromium plated
- Pan: Steel, black powder coated or stainless steel 304

Notes

- Fix pan in circular aperture, mount handle through centre piercing against 'flats' on escutcheon and secure with large brass nut
- Neoprene gasket and stainless spring spacing washer are provided.
- 'FS' keys as standard with 'shuttered' keyway. Optionally 'FT' or 'DLP' key types also available
- Max. recommended torque in pan:
 - Steel: 16 N.m
 - Stainless steel: 22 N.m
- **Contact Gripwell sales for cam pawl and centre-case options**



GB3-G00186SS
(Recess T-handle in special stainless steel pan)



Handles operate through 180° as standard (non-handed), locking in two positions. To special order, rotation can be limited to 90° LH (clockwise) or 90° RH (anticlockwise), when handle will only lock in the rest position. Illustration shows handle with 'flats' vertical on escutcheon.

Part No.	Key	Pan Finish	A	B	C	D	E	F	G	H	J
GB3-G00184	Standard	Black	125	15	15	27	145	32	90	4.75 mm, c/s 9 mm	105
GB3-G00184SS		Stainless Steel									
GB3-G00186	FS880	Black									
GB3-G00186SS		Stainless Steel									
GB3-G00185	Non-Locking	Black									
GB3-G00185SS		Stainless Steel									



Illustration shows recess pan with standard pierced aperture and vertical 'flats'.



Moulded Seal

The edge of the recess pan is embossed, to seat into corresponding groove in moulded seal.

Optional Parts

Part No.	Description
GB3-G00138	Black recessed pan only
GB3-G00939	Black moulded seal only