

GB9 Full 'Plant-On' Mounting T & L-Handle

Features

- Identical to regular 'L' & 'T' models, but with a special high-waisted escutcheon that brings assembly fittings above panel surface, making handles fully 'plant-on'
- Latch systems can be mounted immediately underneath, without need for bridging plate
- 180° rotation as standard, rotation can be limited to 90°, LH/RH, or 360° free-movement. Handles will lock in each 90° position
- Use with latching cams, slam latches or rod systems

Material

- Steel, chromium plated (or black powder coated on request)

Notes

- Increased surface height (to 53 mm) and open fixing at 38 mm centres only
- Fix through countersunk holes, at 38 mm centres only
- Neoprene gasket provided
- 'FS' keys as standard with 'shuttered' keyway. Optionally 'FT' or 'DLP' key types also available
- **Contact Gripwell sales for cam pawl and centre-case options**



Plant-On 'L' Handle

Locking and non-locking, non-handed, with chromium-plated finish. Height 53 mm, all other dimensions as **GB5-00167**

Part No.	Key
GB9-01667	Standard
GB9-01667-01	FS880
GB9-01670	Non-Locking



Plant-On Small 'T' Handle

Locking and non-locking, non-handed, with chromium-plated finish. Height 53 mm, all other dimensions as **GB6-G00140**

Part No.	Key
GB9-01660	Standard
GB9-01660-01	FS880
GB9-01661	Non-Locking



Plant-On Large 'T' Handle

Locking and non-locking, non-handed, with chromium-plated finish. Height 53 mm, all other dimensions as **GB7-G00144**

Part No.	Key
GB9-01664	Standard
GB9-01664-01	FS880
GB9-01665	Non-Locking