

DKA Splined Threaded Insert


Aluminium · Low profile · Splined · Open end
M4 - M10

Features


- Designed to provide load bearing threads in thin sheet materials
- Splined body provides increased torque-to-turn resistance over conventional non-splined inserts
- Reduced tail end diameter offers ease of hole entry
- Low profile head allows near flush fit to application

Material

- Aluminium, clear protective coating



Before Placement



After Placement

Part No.	Thread Size	Grip Range		Hole Size	øA	øB	D	øJ	M	P
		min.	max.	+0.15/-0	max.	±0.25	±0.05	max.	±0.38	max.
DKA-470-2.0	M4 x 0.7 6H	0.5	2.0	6.75	6.73	7.87	0.48	9.91	10.67	7.75
DKA-470-3.3		2.0	3.3						11.94	
DKA-580-3.3	M5 x 0.8 6H	0.5	3.3	7.60	7.52	8.64		11.43	12.07	8.00
DKA-580-5.7		3.3	5.7						14.86	
DKA-610-4.2	M6 x 1.0 6H	0.7	4.2	10.00	9.91	11.56	13.97	14.73	9.65	
DKA-610-6.6		4.2	6.6					17.27		
DKA-8125-3.8	M8 x 1.25 6H	0.7	3.8	13.50	13.46	15.11	0.55	18.80	17.53	11.94
DKA-8125-7.9		3.8	7.9						20.45	
DKA-1015-3.8	M10 x 1.5 6H	0.7	3.8	13.50	13.46	15.11	0.55	18.80	17.53	
DKA-1015-7.9		3.8	7.9						20.45	



Can't find what you are looking for?

We can provide unique and customized solutions.
Contact your nearest [Gripwell](#) team for assistance!