

## G9002 Splined Rivet Nut


Stainless steel 304 · Low profile · Splined · Open end  
M4 - M10

### Features


- Designed to provide load bearing threads in thin sheet materials
- Splined body improves torque-to-turn resistance in softer materials such as aluminium when compared to plain body inserts and improves electrical continuity in sheet metal fixings
- Double diameter body and lead-in chamfer provide easy insertion into hole
- Low profile head allows near flush fit to application

### Material

- Stainless steel 304, natural



Before Placement



After Placement

Part No.	Thread Size	Grip Range		Hole Size	øA	øB	D	øJ	M	P
		min.	max.	+0.1 / -0	max.	max.	±0.13	max.	nom.	max.
G9002-24020	M4 x 0.7	0.25	2.00	6.00	5.97	6.70	0.46	8.80	11.30	7.10
G9002-25030	M5 x 0.8	0.25	3.00	7.00	6.97	7.80	0.46	10.20	12.70	7.90
G9002-26030	M6 x 1.0	0.50	3.00	9.00	8.97	10.20	0.50	12.70	15.30	9.40
G9002-26055		3.00	5.50						17.80	
G9002-28035	M8 x 1.25	0.50	3.50	11.00	10.97	12.20	0.63	15.00	17.30	11.00
G9002-28060		3.50	6.00						19.80	
G9002-20035	M10 x 1.5	1.00	3.50	13.00	12.97	14.20	0.63	17.50	20.40	14.50



### Can't find what you are looking for?

We can provide unique and customized solutions.  
Contact your nearest [Gripwell](#) team for assistance!