

GW316-CLP Low Profile Closed End Threaded Insert


Stainless steel 316 · Low profile · Round · Closed end
M4 - M8

Features


- Designed to provide load bearing threads in thin sheet materials
- Low profile head allows near flush fit to application
- Closed end prevents the ingress of dirt and fluids into thread and electrical circuits
- Extra high corrosion resistance

Material

- Stainless steel 316



Before Placement



After Placement

Part No.	Thread Size	Grip Range		Hole Size	ϕA	ϕB	D	L
		min.	max.	+0.1	-0.02/-0.15	-0.15 / +0.3	-0.05 / +0.3	± 0.35
GW316-CLPM4-0520	M4	0.5	2.0	6.0	6.0	6.5	0.5	15.5
GW316-CLPM5-0530	M5	0.5	3.0	7.0	7.0	7.5	0.5	18.0
GW316-CLPM6-0530	M6	0.5	3.0	9.0	9.0	9.5	0.5	21.5
GW316-CLPM8-0530	M8	0.5	3.0	11.0	11.0	11.5	0.5	24.0

Thread Size	Max. torque	Pull-out	Torque-to-turn	Shear strength
	Nm max.	Kn	Nm	kN
M4	~7.1	> ~11.0	~2.6	~3.5
M5	> ~16.0	> ~14.5	~3.0	~4.8
M6	> ~22.0	> ~27.0	~6.8	~7.3
M8	> ~70.0	> ~40.0	~9.0	~9.0



Can't find what you are looking for?

We can provide unique and customized solutions.
Contact your nearest [Gripwell](#) team for assistance!