

## 9658 Thin Sheet Nutsert


Steel · Low profile · Round · Open end  
M3 - M10

### Features


- Designed to provide load bearing threads in thin sheet materials
- Low profile head allows near flush fit to application

### Material

- Low carbon steel, zinc plated, clear trivalent passivated, lubricated  
(DIN EN 10263-2 Qst 34-3, BS EN/DIN 10263-2 C8C, Werkstoff 1.0213, SAE 1008)



Before Placement



After Placement

Part No.	Thread Size	Grip Range		Hole Size	øA	øB	D	øJ	M	P
		min.	max.	+0.1 / -0	max.	max.	max.	max.	max.	max.
09658-70310	M3 x 0.5	0.51	1.50	4.75	4.72	5.84	0.38	8.40	9.02	5.80
09658-70413	M4 x 0.7	0.51	2.00	6.35	6.32	7.30	0.51	10.30	10.41	7.20
09658-70514	M5 x 0.8	0.51	3.00	7.15	7.11	8.00	0.51	12.70	11.81	7.00
09658-70619	M6 x 1.0	0.76	3.25	9.55	9.50	10.67	0.76	15.50	14.60	9.50
09658-75821	M8 x 1.25	0.91	3.70	10.60	10.57	11.68	0.76	17.20	16.00	10.10
09658-72022	M10 x 1.5	1.00	3.60	14.20	14.17	16.20	0.76	23.30	18.50	10.50

Thread Size	Max. torque	Pull-out	Torque-to-turn	Push-out
	Nm max.	kN	Nm min.	kN
M3 x 0.5	1.5	2.7	0.4	0.8
M4 x 0.7	5.1	6.6	1.9	1.5
M5 x 0.8	7.9	8.0	2.6	1.9
M6 x 1.0	12.4	11.4	3.4	2.4
M8 x 1.25	16.4	15.7	3.6	2.8
M10 x 1.5	33.9	18.7	4.2	3.7